

Specification - LED Screen P4

Parameter		Value
Physical Parameter	LED Type	SMD2525
	Pixel Pitch (mm)	4.8
	Panel Dimensions (WxHxD)/(mm)	500×500×100
	Pixel Per Panel	104×104
	Panel Weight (kg)	9.5
	Panel Material	Die Casting Aluminum
	Module Dimensions (WxH)/(mm)	250×250
Optoelectronic Parameter	Brightness (nit)	4500
	Refresh Rate (Hz)	1920
	Contrast Ratio	/
	Color Temperature (K)	6500
	Viewing Angle (H/V) (°)	140/110
	Driving Type	1/7
	AC Operating Voltage (V)	100~240
	Power Consumption (Max./Avg.)(W/m ²)	750/250
Application Parameter	Storage Temperature (°C)	- 40~+60
	Operating Temperature (°C)	-20~+50
	Storage Humidity (RH)	10 % ~90 %
	Operating Humidity (RH)	10 % ~90 %
	IP Rating (Front/Rear)	IP65/IP54
	LED Lifetime (H)	100000
	Module Maintenance	Front/Rear
	PSU & Others Maintenance	Rear
	Panel Installation Type	Rigging/Stack,Rear Installation
	Riging Quantity (Vertical) (PCS)	20
	Certificate	/

Remark :Power consumption tolerance: ±15%, according to the actual situation.